



Product card

Soft UV Painter's Tape

index	
	5146, 5067, 5068, 5069

1. Application

For protecting surfaces during painting, including outdoor conditions.

2. Technical Data

- Material: Polyethylene with paper admixture
- Adhesive: Acrylic
- Color: Blue
- Width [mm]: 25, 30, 38, 48
- Length [m]: 50
- Thickness of PE foil: 80µm
- Total thickness: 110µm
- Amount of adhesive: 23g/m²
- UV resistance: 14 days

3. Risk Analysis

- Risk of weakened adhesion: Incorrect application conditions may reduce bonding efficiency.
- Risk of surface damage: Leaving the tape on for too long may cause removal issues.
- Risk of tape tearing: Improper unwinding can cause damage.
- Risk of residu

4. Safety Guidelines

- Use as intended on clean, dry surfaces.
- Do not exceed the recommended UV exposure time.
- Remove tape slowly to avoid surface damage.
- Avoid tape contact with moisture before application.
- Keep out of reach of children.
- Store in proper conditions

5. Storage Conditions

This document was electronically generated, does not require a signature.

All rights reserved. The card may be shared only in the original form in which it was received. No fragment presented in this document may be modified in any way or distributed in partial form without prior permission. The photos used are for preview purposes. Update date: 13.12.2024.

Store in a dry and cool place, away from UV rays and moisture.



FHU Partner Ljajić Milan
ul. Pocztowa 32
83-034 Trąbki Wielkie, Poland
VIES: PL5831117693