

Product card



Double-Sided Reinforced Tape

| | |
|-------|------------------|
| index | 5052, 5053, 5054 |
|-------|------------------|

1. Application

For durable bonding of medium and heavy materials in construction, renovation, and assembly works. For fastening carpets.

2. Technical Data

- Material: Fiber-reinforced polyester
- Adhesive: Synthetic rubber
- Liner: Honey paper, silicone 50µm
- Color: Transparent
- Width [mm]: 48
- Length [m]: 5, 10, 25
- Total thickness: 140µm

3. Risk Analysis

- Improper application: Risk of weak bonding if proper pressure is not applied.
- Surface damage: Potential adhesive residue when tape is removed.
- Tape breakage: Excessive load may cause tearing.
- Adhesive contact: Adhesive may cause skin irritation.
- Property loss: Improper storage may weaken adhesive properties.

4. Safety Guidelines

- Apply on clean, dry surfaces.
- Ensure proper pressure during application.
- Avoid excessive load on the tape.
- Do not use on high-temperature surfaces.
- Keep out of reach of children.
- Use scissors or a knife for precise cutting.

5. Storage Conditions

Store in a dry and cool place, away from moisture and heat sources.



FHU Partner Ljajić Milan
ul. Pocztowa 32
83-034 Trąbki Wielkie, Poland
VIES: PL5831117693