



## Product card

Spiked Roller for Self-Leveling Floors

index	
	5663, 5664, 5666

### 1. Application

Used for air venting of thin-layer self-leveling floors, mortars, and fillers.

### 2. Technical Data

- Roller: Polyethylene
- Plastic parts: Polypropylene
- Frame: Chrome-plated iron
- Spike height: 14 cm, 28 cm
- Roller length: 25 cm, 50 cm

### 3. Risk Analysis

- Risk of clogging the roller: Clogging may occur if excess material is used.
- Minimizing the risk: Use the roller evenly, controlling the amount of material applied.
- Risk of surface damage: Improper use of the roller may damage the floor surface.
- Minimizing the risk: Use the roller with appropriate pressure to avoid damaging the surface.
- Risk of contact with sharp elements: Contact with the roller's spikes may cause injury.
- Minimizing the risk: Store the roller in a safe place and avoid contact with the body.

### 4. Safety Guidelines

- Use as intended.
- Keep out of reach of children.
- Clean the roller after each use to prevent clogging of the spikes.
- Use the roller with appropriate pressure.

### 5. Storage Conditions

Store in a dry place, away from moisture.



FHU Partner Ljajić Milan  
ul. Pocztowa 32  
83-034 Trąbki Wielkie, Poland  
VIES: PL5831117693