

Product card



Super Duct Tape

index	5093
-------	------

1. Application

For securing, sealing, and repairing surfaces during construction and renovation works, weather-resistant. It is used in internal and external applications.

2. Technical Data

- Material: PE coated fabric
- Adhesive: Hotmelt / Synthetic rubber
- Color: Silver
- Width [mm]: 48
- Length [yd]: 50
- Mesh density (fibers): 32
- Total thickness: 220µm
- Possibility of manual tearing

3. Risk Analysis

- Improper usage: Risk of tape detaching in harsh conditions.
- Prolonged skin contact: May cause irritation.
- Tape overload: Possibility of tearing.
- Adhesive residue: Risk of leaving marks on surfaces.
- Exposure to extreme temperatures: Loss of adhesive properties.

4. Safety Guidelines

- Use only on clean, dry, and smooth surfaces.
- Avoid overstretching the tape during application.
- Do not leave the tape on surfaces longer than necessary.
- Keep out of reach of children.
- Do not use on hot surfaces.
- Protect the tape roll from dirt after use.

5. Storage Conditions

Store in a cool, dry place, away from heat sources and sunlight.



FHU Partner Ljajić Milan
ul. Pocztowa 32
83-034 Trąbki Wielkie, Poland
VIES: PL5831117693